

## FTxx\*1)P1Gy\*2)

e.g. FT15P1G1


- \*1) xx No. of contacts 09, 15, 25 or 37
- \*2) y for performance classes 1, 2 or 3  
(contact cycle for G1/G2/G3 = 500/200/50)

xx	A [mm]	B [mm]	C [mm]	*E [mm]
09	30.8	16.9	25	ø1
15	39.1	25.2	33.3	
25	53	38.9	47.04	
37	69.3	55.3	63.5	

RoHS compliant

\*PCB hole patterns, øE on supplement AM0023

No.	St.	Part	Type	Description/Material	Surface plating/Colour/Class
4	2	Clinch nut	FT 4-40 / Steel		tin plated
3	xx	Signal contact	P1 / Brass		G1/G2/G3
2	1	Shell	Steel		tin plated
1	1	Insulator	PBT (-55°C - +125°C)		white



Measurement without tolerance occ. to ISO 2768-m

SCALE 2:1

TITLE

D-Sub Miniature Steckverbinder

NAME / DATE  
DRAWN schref 17-07-2002  
CHECKED floßmann 17-07-2002

**FCT**  
a molex company

DWG.NO.

FTxxP1Gy

REV.

1

REV. DATE CH.-NO.

ORIGINAL: DIN A3-DRAWING AS A FILE

REPLACEMENT FOR:

PAGES 1