



Fxx*1)S1Gy*2)-0982

e.g. F25S1G3-0982

RoHS compliant

- *1) xx No. of contacts 09, 15, 25 or 37
- *2) y for performance classes 1, 2 or 3 (contact cycle for G1/G2/G3 = 500/200/20)

xx	A [mm]	B [mm]	C [mm]	*E [mm]	*F [mm]
09	30.8	16.4	25	ø1	ø3
15	39.1	24.7	33.3		
25	53	38.5	47.04		
37	69.3	54.9	63.5		

*PCB hole patterns, øE, øF on supplement AM0023

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
4	2	Snap-in bolt	PCB 1.6mm / Brass	tin plated
3	xx	Signal contact	S1 / Brass	G1/G2/G3
2	1	Shell	Steel	tin plated
1	1	Insulator	PBT (-55°C - +125°C)	white



Measurement without tolerance occ. to ISO 2768-m

SCALE 2:1

TITLE

NAME / DATE
 DRAWN Denzinger 20-02-2003
 CHECKED Floßmann 24-02-2003

D-Sub Miniature Connector



DWG.NO. FxxS1Gy-0982 REV. 1

COMMENT: ALL RIGHTS ARE RESERVED BY US FOR THIS DRAWING. WITHOUT OUR PRIOR CONSENT, IT MAY NEITHER BE DUPLICATED NOR MADE AVAILABLE TO A THIRD PARTY. AND IT ALSO MAY NOT BE IMPROPERLY USED BY THE RECEIVER, OR A THIRD PARTY.